SLIDE SWITCH

ALPHA

Application

- ✓ TV/Video, Audio, Home appliance, Precision apparatus, Automotive, Office equipment, Communication, Musical instruments, Industrial control



Feature

- ✓ Low profile slide switches available for various fields.

■Specification

Operating Temperature Range	-10 °C~70°C
Standard Contact Resistance	25mΩ max.
Operating Life Cycle	10,000 cycles

■How to order

SV70050F - 0202 - 6T - N

Model

Number of Pole & Position
Ex. 0202 – 2 poles 2 positions

Lever Type

Timing

Order Code	Description
N	Non-shorting (break-before-make)
F	Free (Undefined)

■Model Description

Model	Lever Length	Operating Direction	Rating	Timing
SS57010F-0102	2.5	Vertical	AC125V 0.3A	Non-shorting
SS65010F-0203	4.5, 9	Vertical	DC50V 0.5A	Free
SS70010F-0202	3.5, 4, 5, 6, 7.5, 10, 12, 14	Vertical	AC125V 0.3A	Non-shorting
SS70020F-0202		Vertical	AC125V 0.3A	Non-shorting
SS71020F-0203	6, 9	Vertical	AC125V 0.3A	Non-shorting
SS84017F-0403	5.3	Vertical	AC125V 0.3A	Free
SS13010F-0202	0, 8	Vertical	AC125V 0.3A	Non-shorting
SV65020F-0203	6	Horizontal	AC125V 0.3A	Free
SV68010F-0203	4, 6	Horizontal	AC125V 0.3A	Free
SV69010F-0202	4, 6	Horizontal	AC125V 0.3A	Non-shorting
SV70050F-0202	6, 10, 20	Horizontal	AC125V 0.3A	Non-shorting
SV71010F-0202	6	Horizontal	DC30V 0.1A	Non-shorting

Order Code	Outline Drawing
SS57010F-0102-2.5T	
SS65010F-0203-□H	

Back to top

Order Code	Outline Drawing
SS70010F-0202-□T	
SS70020F-0202-□T-021	
SS70010F-0202-□T-011 	
SS71020F-0203-□T-025	

Back to top

Order Code	Outline Drawing
SS84017F-0403-□T 	
SS13010F-0202-0 	
SV65020F-0203-□H-01 	
SV68010F-0203-□V 	

Back to top

Order Code	Outline Drawing
SV69010F-0202-□V	
SV70050F-0202-□T	
SV71010F-0202-□T	

Design and specifications presented here are for the standard parts only. Please kindly contact us for your special requests and ask for the current technical specifications before purchase and/or use.

Back to top